	Regi	stration No :			,						1				
Tota	al Nu	mber of Pages : 02									in the				B.Tech
														1	PET5I101
		5 th Ser	neste			r / Back			natio	on 2	019-	-20			
						ROL S									**
				E		CH : E									
						Marks									
						ne : 3 H									
Λn	ewo.	r Question No.1 (Pa	rt_1\	white		DE : H			v El	GH	T fre	m P	art-II	and a	ny TWO
All	iswe	Question No.1 (Fa	11-1)	WIII		om Par		, an	у С	GH	1.110	ALSO CO	art-ii	anu a	dy IVVO
		The figu	ıres i	n th	e righ	nt hand	mar	gin	indi	cate	e ma	ırks.			
						Part-									
Q1		Only Short Answer								1.729					(2×10)
	a)	Differentiate between										11-1		V250 (CLUCK)	
	b)	Write down the magnitude criterion and the angle criterion for a point to be on the root locus. How is the gain K at a particular location determined?													
	c)	What are the two spe						Sittiff	ileu:						
	d)							ack o	contr	ol sy	sten	n?			
	e)	Define words and equation, the sensitivity of feedback control system? What is the effect of the negative feedback on time constant and bandwidth of the system?													
	f)	Explain Nquist Criteri													
	g)	State the analogous quantities for mechanical rotational system and electrical systems													
	61	in force-voltage analogy.													
	h) i)	Distinguish between transfer function and frequency transfer function? Why Nichols chart is used?													
	j)	Given the following polynomial equation $s^3 + 5.5s^2 + 8.5s + 3 = 0$. Determine the number of roots of the polynomial which have real parts strictly less than													
						Part-	п								
Q2	a) b)	Only Focused-Short Explain the constant				Questio	ns- (V	4 1 1 1 1 1		t of Tv	welve)	(6 × 8)
													. W	here k	<
		The open loop transfer function of a unity feedback system is $(S) = \frac{K}{S(ST+1)}$. Where K and T are constants. How many times the gain should be increased to increase the overshoot from 50% to 60%.													
	20							Y	(2)		1				
	c)	The transfer function													
	77547	input is a unit step signal. Identify the transient and the steady state components of the output response Using final value theorem find the steady state value of y(t).													
	d)	Sketch the bode plot	of op	en lo	op trai	nsfer fur	ction	IS G	(s)H	l(s)	E	- K-		and the	T6
		gain margin and phas	se ma	rgin.					-0.						
	e)	Consider a system d	escrib	ed b	y a dif	ferential	equa	tion	$\frac{d}{dt}$	+ 2	dv dr	251	50x(() First	d
		out the time domain t	behav	ior a	nd the	maximu	m ou	tput	for a	2.5	unit	step	NACT.		
	f)	For a unity feedback	2000	nd o	order s	evetam v	whose	00	on k	oon	trans	efor to	incher	26451	
		$\frac{4}{s(s+2)}$. Determine th	e ma	xim	um ov	ershoot	and	the	tim	e to	rea	ich !	he m	AXIN' I	87

overshoot when step displacement of 18° is given to the system. Find the rise time,

delay time and settling time for a steady state error of 7%.

x 10)